



Solution details		Sentera products					
<p>The AC fan will be controlled based on the pressure level.                      The pressure setpoint and other parameters of the HPSPF pressure controller can be modified via Modbus RTU communication.                      TK monitoring for thermal motor protection.</p> <p>Suited for motor type: 230 VAC voltage controllable motors with TK motor protection                      Motor control: Electronic fan speed controller                      Minimum motor speed: Make sure that the minimum voltage remains high enough to avoid stalling of the motor.                      Maximum motor current: 1,5 A</p>		<table border="1"> <thead> <tr> <th>Article code</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>SEPS8-24-40 EVSS1-15-DM HPSPF-1K0-2</td> <td>24 VDC power supply Electronic fan speed controller Differential pressure, air flow controller</td> </tr> </tbody> </table>	Article code	Description	SEPS8-24-40 EVSS1-15-DM HPSPF-1K0-2	24 VDC power supply Electronic fan speed controller Differential pressure, air flow controller	
Article code	Description						
SEPS8-24-40 EVSS1-15-DM HPSPF-1K0-2	24 VDC power supply Electronic fan speed controller Differential pressure, air flow controller						
		External products					
		AC fan with a voltage controllable motor I <sub>max</sub> 1,5 A					

Consult the fan manufacturer for the correct wiring